

# Air Handling Unit 30000 m<sup>3</sup>/h - 250 kW <sup>(1)</sup>

Model	CCEB DG 9
Cooling capacity (kW) Air 35°C/40%, water 7/12°C	250
Water flow & pressure drop (l/s) & (Kpa)	11,94 & 23,24
Heating capacity (kW) Air -15°C/90%, water 45/40°C	393
Water flow & pressure drop (l/s) & (Kpa)	11,94 & 23,24
Nominla air flow (m3/h)	30000
Available external static pressure (Pa)	500



Electrical data	
Power supply (V/Ph/Hz)	400/3/50
Fan motor (kW)	15
Fan motor (A)	28
Electrical heating (kW)	2 x 147
Electrical heating (A)	2 x 212

Connections	
Cooling coil	3 inches
Dimensions supply (mm)	1830 x 1830
Dimensions return (mm)	855 x 1830

Dimensions & Weight	
Length (mm)	4247
Width (mm)	2060
Height (mm)	2080
Weight (kg)	2063

Unit Configuration	
Cooling coil	1 X
Electrical heating	1 X
Pre filter	G4
Bag filter	Varicel V XLO F7/F7
Speed control	TR200 P15K

Trane optimizes the performance of homes and buildings around the world. A business of Ingersoll Rand, the leader in creating and sustaining safe, comfortable and energy efficient environments, Trane offers a broad portfolio of advanced controls and HVAC systems, comprehensive building services, and parts. For more information, visit [www.Trane.com](http://www.Trane.com).

Trane has a policy of continuous product and product data improvement and reserves the right to change design and specifications without notice.

© 2014 Trane All rights reserved

(1) At Eurovent conditions: 12/7°C entering/leaving water temperature and 35°C ambient air temperature

We are committed to using environmentally conscious print practices that reduce waste.